






SEEGNUS MW SLT

1280x1024 - 7.5µm



THE FIRST 7.5µM PITCH SXGA DETECTOR WITHIN THE PLUGUP PLATFORM



HIGH IMAGE QUALITY



HIGH RESOLUTION



COMPACTNESS



EASY MECHANICAL INTEGRATION



MOBILE

HTTI

GROUND















MULTI-PURPOSE





LOW POWER



COMPACT



WEIGHT



LOW ACOUSTIC **NOISE**

●● THE FIRST 7.5µM PITCH SXGA DETECTOR WITHIN THE PLUGUP PLATFORM ••

PRODUCT EMBEDDED FEATURES	
IDDCA + PROXIMITY BOARD + CRYOCOOLER CONTROLER	
ARRAY FEATURES	
Detector spectral response	■ 3.6 to 4.2 µm
FPA operating temperature	■ Up to 150 K
ROIC (READ-OUT INTEGRATED CIRCUIT)	
Selection	■ IWR and ITR
ROIC architecture	Direct Injection
ROIC functionalities	Invert/Revert
Windowing modes	■ Down to 160 x 2
Frame rate	■ Up to 60Hz
TYPICAL PERFORMANCES	
NETD	■ 40mK (300K, 50%WF, f/3)
Array operability	> > 99.5%
RFPN at 50% well fill	< 0.5 × RMS noise
INTERFACES	
Video output	■ CameraLink [®] Base Mode
Communication	■ CameraLink® UART
Product Power Supply	■ 12 Vdc typical
PHYSICAL CHARACTERISTICS	
Maximum Outline dimensions (LxWxH)	■ 56 mm x 77 mm x 72.5 mm
Weight	■ 360 g
K588	
Aperture	• f/4, f/3.4, f/3, f/2
Regulated Input power @20°C	■ <3.5Wdc
Cooldown Input power @20°C	■ <15Wdc
Cooldown time @20°C	■ <4min
Cooler MTTF	3 2,000hrs

AVAILABLE SERVICES

Technical training and support








info@lynred.com

Recognition distances for human measuring 1.80 m x 0.50 m



 $Range\ for\ Johnson's\ criteria,\ target\ delta T=2\ K,\ perfect\ atmospheric\ and\ optics\ transmissions,\ theoretical\ square\ pixel.$

LYNRED HEADQUARTERS Avenue de la Vauve - CS 20018 91127 Palaiseau - France Phone +33 (0)1 60 92 18 30 info@lynred.com

DEVELOPMENT AND PRODUCTION CENTER Actipole - CS 10021 - 364, route de Valence 38113 Veurey-Voroize - France Phone +33 (0)4 76 28 77 00

LYNRED ASIA PACIFIC PTE LTD 5 Shenton way, #22-04 UIC Building 068808 Singapore info@lynred.com

LYNRED USA 373 US Highway 46W Fairfield, NJ 07004, USA Phone +1 973.882.0211 info@lynred-usa.com