





AstroScope™

for Nikon and Canon Mirrorless Cameras

FOR EXPORT ONLY

NIGHT VISION ADAPTER

Convert your high-performance Nikon and Canon Mirrorless camera and lens into a military grade night vision system for video and image capabilities. Enabling your Mirrorless camera with GEN-3 night vision technology. Transform dark scenes into bright, high-resolution images. AstroScopeTM is an essential tool for today's night vision photographer.

ENHANCE YOUR VISIBILITY IN LOW LIGHT / NO LIGHT

- POWERED BY CAMERA BATTERY
- QUICK-CONNECT / DISCONNECT
- PRESERVES CAMERA SETTINGS & LENS CONTROL
- NO ADDITIONAL CABLES OR CHARGING
- WHITE PHOSPHOR OR GREEN PHOSPHOR OPTIONS AVAILABLE

SURVEILLANCE

LEISURE

DEFENSE







●● CONVERT YOUR MIRRORLESS CAMERA INTO A HIGH-PERFORMANCE NIGHT VISION SYSTEM ●●







Law Enforcement



Surveillance



Wildlife Management











CANON EOS R6 MARK II MIRRORLESS CAMERA + ASTROSCOPE™ CONFIGURATION



PRODUCT DESCRIPTION

9400EOS-3VM-1600WP

9400EOS-3VM-1800WP

9400EOS-3VM-2000WP

9400EOS-3VM-2200WP

9400EOS-3VM-1600GP

9400EOS-3VM-1800GP

9400EOS-3VM-2000GP

9400EOS-3VM-2200GP

9400NIKSP-3VM-1600WP

9400NIKSP-3VM-1800WP

9400NIKSP-3VM-2000WP

9400NIKSP-3VM-2200WP

9400NIKSP-3VM-1600GP

9400NIKSP-3VM-1800GP

9400NIKSP-3VM-2000GP

9400NIKSP-3VM-2200GP

Additional parts upon request.

NIKON Z-MOUNT MIRRORLESS CAMERA + ASTROSCOPE™ CONFIGURATION

Without AstroScope™



With AstroScope™

GENERAL SPECIFICATIONS		
Device Weight	■ 574g*	
Dimensions	■ 6.95 cm x 12.78 cm	
Intensifier	Generation 3 mil-spec, 18 mm GaAs, MCP	
Lifetime	>12,000 hours continuous use	
Power Requirements	<300mW (<50mA typical)	
Lens Compatibility	RF Mount (Canon), Z Mount (Nikon)	
Frame	■ Full, 1.6 (Canon), FX, DX (Nikon)	
Warranty	1 Year, workmanship and materials	

CANON/NIKON

EOS

EOS

EOS

EOS

EOS

EOS

EOS

EOS

NIK

NIK

NIK

NIK

NIK

NIK

NIK

NIK

*Typical

GAIN

VARIABLE VARIABLE

VARIABLE

VARIABLE

VARIABLE

VARIABLE

VARIABLE

VARIABLE

VARIABLE

VARIABLE

VARIABLE

VARIABLE

VARIABLE

VARIABLE

VARIABLE

VARIABLE

PHOSPHOR

WHITE

WHITE

WHITE

WHITE

GREEN

GREEN

GREEN

GREEN

WHITE

WHITE

WHITE

WHITE

GREEN

GREEN

GREEN

GREEN

	oto)	
	10 P.	T. ST.
4	and special	

Both shots were taken using the same camera settings

Shutter Speed: 1/40; No Flash; Lens Aperture: F/5; Focal Length: 52 mm; ISO: 800; Exposure Comp: 0

Standard Lead Time: 4 Weeks, Call for Pricing.

Export of this product is controlled by the US State Department. Prior authorization is required for re-export or transfer.

LYNRED HEADQUARTERS
Avenue de la Vauve - CS 20018
91127 Palaiseau - France
Phone +33 (0)1 60 92 18 30
info@lynred.com

DEVELOPMENT AND PRODUCTION CENTER
Actipole - CS 10021 - 364, route de Valence
38113 Veurey-Voroize - France
Phone +33 (0)4 76 28 77 00
info@lynred.com

LYNRED ASIA PACIFIC PTE LTD 5 Shenton way,

FEATURED PRODUCTS

BODY TYPE

MIRRORLESS

MIRRORLESS

MIRRORLESS

5 Shenton way, #22-04 UIC Building 068808 Singapore info@lynred.com LYNRED USA 373 US Highway 46W Fairfield, NJ 07004, USA Phone +1 973.882.0211 info@lynred-usa.com